



Dimension (with case)

Length	151mm
Width	98,5mm
Height	95mm
Weight	1,70kg

Electrical Specification


Nominal Voltage	12V (12,8V)
Nominal Capacity	12Ah (c20)
Energy	154 Wh
Resistance	≤ 60mΩ
Self discharge	<3% / month
Life Cycle	≤2500 times @ 25°C / 80% DOD

Charge Specifications

Recommended charge current	6A
Max. charge current	15A
Recommended charge voltage	14,6V
Max. Charge Voltage	14,8V
Charge mode	CC/CV
Overcharge Protection Voltage	14,9V - 15,2V
Charge temperature	0°C ~ +50°C


Discharge Specifications

Max. continious discharge current	25A
Puls current (≤5s)	40A
BMS discharge cut-off	10V
Short-circuit protection (<10ms)	approx. 140A
Discharge temperature	-20°C ~ +60°C



Mechanical Specifications

Case material	ABS
Terminal type	Faston 6,3
Enclosure protection	IP65
Cell type	cylindrical



Always refer to the latest edition of the Technical Manual for a safe usage. This and more useful downloads, such as product catalogs, material safety data sheet (MSDS), etc. can be found on our website www.airbatt.de

© 2021 ACCU-24 Batterien & Systeme GmbH
All rights reserved. All trademarks are the property of their respective owners.
All data subject to change without notice.