



## Handling and Storage

- Can be mounted or stored in any orientation except inverted
- 2-years storage life at 77°F (25°C) without needing to charge. Recharge when the OCV is <12.2V (50% SOC).
- Classified as non-spillable and approved as non-hazardous cargo for ground, sea and air transportation in accordance with the requirements of IMDG (International Maritime code for Dangerous Goods) and ICAO (International Civil Aviation Organisation)

## Charging and Self-Discharge

|                                          |                     |
|------------------------------------------|---------------------|
| Cyclic Charge Voltage                    | 14.4 - 14.8V @ 25°C |
| Float Charge Voltage                     | 13.5 - 13.8V @ 25°C |
| Charger voltage at 68°F (20°C)           | 14.4V to 14.8V      |
| Self-discharge per month at 68°F (20°C)  | 1.25%               |
| Self-discharge per month at 104°F (40°C) | 5%                  |
| 80% depth of discharge cycles            | 400                 |

## Accreditations

The management systems governing the manufacture of this product are ISO 9001 and ISO 14001 certified.

\*Cold Start Performance S.A.E J537 Apr 2016

# Technical Data Sheet

## ODS-AGM15L

- Group 15 Absorbed Glass Mat (AGM) battery with Thin Plate Pure Lead (TPPL)
- Up to 400 cycles at 80% depth of discharge
- Advanced dual purpose battery for engine start and deep cycle use

## Power and Performance

|                                           |               |
|-------------------------------------------|---------------|
| Voltage                                   | 12V           |
| Pulse (5 second) Hot Cranking Amps (PHCA) | 460A          |
| Cold Cranking Amps (CCA)                  | 150A          |
| HCA                                       | 280A          |
| MCA                                       | 220A          |
| 20Hr Nominal Capacity (Ah)                | 13Ah          |
| 10Hr Nominal Capacity (Ah)                | 12Ah          |
| Reserve Capacity Minutes                  | 18 mins       |
| Terminal                                  | M6 Receptacle |
| Torque Spec in-lbs (Nm max)               | 50 (5.6)      |
| Internal Resistance (mΩ)                  | 10 mΩ         |
| Short Circuit (A)                         | 1200A         |
| Recommended Min. Charging Current (A)     | 1.2A          |
| UPC                                       | 635241140965  |




## Dimensions and Weight

|                             |                   |
|-----------------------------|-------------------|
| Length                      | 6.9 in / 175 mm   |
| Width                       | 3.3 in / 84 mm    |
| Height (terminals included) | 4.9 in / 124 mm   |
| Height (container)          | 5.1 in / 130 mm   |
| Weight                      | 11.4 lbs / 5.2 kg |

See Line Drawing on next page

## Temperature

|                             |                                |
|-----------------------------|--------------------------------|
| Operating temperature range | -40°F / -40°C to 113°F / +45°C |
| Optimum storage temperature | 68°F / +20°C                   |

**ODS-AGM15L****Line Drawing****ODS-AGM15L  
RIGHT POSITIVE  
FEMALE TERMINAL****ODYSSEY batteries – AGM<sup>2</sup> Thin Plate Pure Lead (TPPL) Technology**

ODYSSEY<sup>®</sup> AGM<sup>2</sup> Thin Plate Pure Lead (TPPL) batteries feature 99% pure lead plates that are extremely thin, so more of them fit into the battery. More plates mean more power – ODYSSEY AGM<sup>2</sup> TPPL batteries deliver twice the power and three times the service life of any other conventional battery, outperforming standard AGM or SLI (flooded) batteries in terms of power density, fast-charge acceptance, shelf life, durability and most important – value for your money.

Technical Data Sheet correct at time of exporting PDF. Please check website for updates.