



Handling and Storage

- Can be mounted or stored in any orientation except inverted
- 2-years storage life at 77°F (25°C) without needing to charge. Recharge when the OCV is <12.2V.
- Classified as non-spillable and approved as non-hazardous cargo for ground, sea and air transportation in accordance with the requirements of IMDG (International Maritime code for Dangerous Goods) and ICAO (International Civil Aviation Organisation)

Charging and Self-Discharge

Cyclic Charge Voltage	14.4 - 14.8V @ 25°C
Float Charge Voltage	13.5 - 13.8V @ 25°C
Charger voltage at 68°F (20°C)	14.4V to 14.8V
Self-discharge per month at 68°F (20°C)	1.25%
Self-discharge per month at 104°F (40°C)	5%
80% depth of discharge cycles	400

Accreditations

The management systems governing the manufacture of this product are ISO 9001 and ISO 14001 certified.

*Cold Start Performance S.A.E J537 Apr 2016

Technical Data Sheet

ODP-AGMDINB

- Absorbed Glass Mat (AGM) with Thin Plate Pure Lead (TPPL) dual purpose battery for engine start and deep cycle use

Power and Performance




Voltage	12V
Pulse (5 second) Hot Cranking Amps (PHCA)	2400A
Cold Cranking Amps (CCA)	1300A
HCA	1747A
MCA	1549A
20Hr Nominal Capacity (Ah)	170Ah
10Hr Nominal Capacity (Ah)	153Ah
Reserve Capacity Minutes	370 mins
Terminal	SAE
Torque Spec in-lbs (Nm max)	60 (6.8)
Internal Resistance (mΩ)	2.0 mΩ
Recommended Min. Charging Current (A)	15.3A

Dimensions and Weight

Length	20.39 in / 518 mm
Width	8.78 in / 223 mm
Height (terminals included)	8.58 in / 218 mm
Height (container)	8.28 in / 210 mm
Weight	117.3 lbs / 53.2 kg

See Line Drawing on next page

Temperature

Line Drawing**ODP-AGMDINB
LEFT POSITIVE
SAE TERMINALS****ODYSSEY batteries – AGM² Thin Plate Pure Lead (TPPL) Technology**

ODYSSEY® AGM² Thin Plate Pure Lead (TPPL) batteries feature 99% pure lead plates that are extremely thin, so more of them fit into the battery. More plates mean more power – ODYSSEY AGM² TPPL batteries deliver twice the power and three times the service life of any other conventional battery, outperforming standard AGM or SLI (flooded) batteries in terms of power density, fast-charge acceptance, shelf life, durability and most important – value for your money.

Technical Data Sheet correct at time of exporting PDF. Please check website for updates.