

Sprechen Sie uns an:



## intAct Block-Power

Supply batteries | Stand by  
Sealed AGM block batteries



# intAct Block-Power

Supply batteries | Stand by  
Sealed AGM block batteries

The intAct Block-Power series batteries are mainly used in alarm systems. However, they also serve as absolutely reliable energy storage for safety power supply systems, safety illumination and

for a number of hobby uses. In addition, these batteries are suitable for minor traction applications such as wheelchairs as well as rehabilitation clinics.

## Capacity c20 – Designlife 5 years

| Battery  | Capacity c20 | Position of terminal | Connectors | VDS proofed | Weight kg | Dimensions mm L x B x H |
|----------|--------------|----------------------|------------|-------------|-----------|-------------------------|
| BP6-1.2  | 6 V 1.2 AH   | + -                  | S          |             | 0,3       | 97 x 25 x 56            |
| BP6-4    | 6 V 4 AH     | - +                  | S          |             | 0,9       | 70 x 47 x 106           |
| BP6-7    | 6 V 7 AH     | + -                  | S          |             | 1,3       | 151 x 34 x 100          |
| BP6-10   | 6 V 10 AH    | + -                  | S          | VDS         | 2,0       | 151 x 50 x 100          |
| BP6-20   | 6 V 20 AH    | + -                  | G-M5       |             | 3,4       | 157 x 83 x 125          |
| BP12-1.2 | 12 V 1.2 AH  | + -                  | S          | VDS         | 0,6       | 97 x 45 x 59            |
| BP12-2.1 | 12 V 2.1 AH  | + -                  | S          | VDS         | 0,9       | 178 x 35 x 64           |
| BP12-2.9 | 12 V 2.9 AH  | - +                  | S          |             | 1,1       | 79 x 56 x 102           |
| BP12-3.5 | 12 V 3.5 AH  | - +                  | S          |             | 1,3       | 134 x 67 x 64           |
| BP12-4   | 12 V 4 AH    | - +                  | S          |             | 1,5       | 90 x 70 x 106           |
| BP12-7   | 12 V 7 AH    | - +                  | S          | VDS         | 2,5       | 151 x 65 x 98           |
| BP12-10  | 12 V 10 AH   | - +                  | S          |             | 3,4       | 151 x 65 x 112          |
| BP12-12  | 12 V 12 AH   | - +                  | S          | VDS         | 3,8       | 151 x 98 x 98           |
| BP12-17  | 12 V 17 AH   | - +                  | G-M5       | VDS         | 5,6       | 181 x 76 x 167          |
| BP12-22  | 12 V 22 AH   | - +                  | G-M5       |             | 5,8       | 181 x 76 x 167          |
| BP12-26N | 12 V 26 AH   | - +                  | G-M5       | VDS         | 9,4       | 166 x 175 x 125         |
| BP12-26  | 12 V 26 AH   | - +                  | G-M5       |             | 9,4       | 166 x 125 x 175         |
| BP12-33  | 12 V 33 AH   | + -                  | G-M6       |             | 9,7       | 195 x 130 x 180         |

## Capacity c10 – Designlife 10-12 years

| Battery  | Capacity c10 | Position of terminal | Connectors | VDS proofed | Weight kg | Dimensions mm L x B x H |
|----------|--------------|----------------------|------------|-------------|-----------|-------------------------|
| BP12-38  | 12 V 38 AH   | - +                  | G-M6       | VDS         | 13.5      | 197 x 165 x 170         |
| BP12-50  | 12 V 50 AH   | - +                  | G-M6       |             | 14.8      | 197 x 166 x 175         |
| BP12-60  | 12 V 60AH    | - +                  | G-M6       |             | 21.0      | 276 x 175 x 190         |
| BP12-65  | 12 V 65 AH   | + -                  | G-M6       | VDS         | 22.0      | 350 x 165 x 178         |
| BP12-75  | 12 V 75 AH   | + -                  | G-M6       |             | 23.8      | 260 x 170 x 210         |
| BP12-100 | 12 V 100 AH  | + -                  | G-M8       |             | 31.0      | 330 x 173 x 220         |
| BP12-120 | 12 V 120 AH  | + -                  | G-M8       |             | 38.0      | 410 x 177 x 225         |
| BP12-140 | 12 V 140 AH  | + -                  | G-M8       |             | 45.0      | 344 x 171 x 280         |
| BP12-150 | 12 V 150 AH  | + -                  | G-M8       |             | 48.0      | 485 x 170 x 242         |
| BP12-200 | 12 V 200 AH  | + -                  | G-M8       |             | 66.0      | 522 x 240 x 224         |

**Product line:** 12 V + 6 V AGM batteries  
**Model:** AGM technology, grid plates, sealed, completely maintenance-free  
**Status:** GUG = Filled and charged  
**Quality:** OEM quality  
**Purpose:** Morate cyclic use  
**Storage life:** Up to 12 months  
**Designlife:** For BP 12 – 33 and lower  
= 5 years  
From BP 12 – 38 and up  
= 12 years

**Type of terminal:** S = 4.8 mm fast-on plug-in contact  
G = threaded connection – drilled flat contact  
**Properties:** Low self-discharge, completely maintenance free  
**Use:** Alarm systems – smoke alarms – safety illumination – electric wheelchairs – mobile lifting platforms – cleaning equipment – solar applications – construction site illumination  
**Cycle stability:** BP 12 - 50 = extra cycle-proof  
BP 12 - 75 = extra cycle-proof

# intAct Block-Power

Supply batteries | Stand by  
Sealed AGM block batteries

The intAct Block-Power series batteries are mainly used in alarm systems. However, they also serve as absolutely reliable energy storage for safety power supply systems, safety illumination and

for a number of hobby uses. In addition, these batteries are suitable for minor traction applications such as wheelchairs as well as rehabilitation clinics.

## SP/SPG High Performance – Longlife by Eurobat 10-12 years

| Battery   | Capacity c10 | Position of terminal | Connectors | Weight kg | Dimensions mm<br>L x B x H |
|-----------|--------------|----------------------|------------|-----------|----------------------------|
| SP12-9    | 12 V 8,4 AH  | - +                  | S          | 2,7       | 151 x 65 x 98              |
| SP12-12   | 12 V 11 AH   | - +                  | S          | 3,6       | 151 x 99 x 100             |
| SP12-18   | 12 V 16,7 AH | - +                  | G-M5       | 5,3       | 181 x 76 x 166             |
| SPG12-45  | 12 V 45 AH   | - +                  | G-M6       | 14,00     | 196 x 165 x 170            |
| SPG12-55  | 12 V 55 AH   | + -                  | G-M6       | 17,20     | 228 x 138 x 213            |
| SPG12-65  | 12 V 65 AH   | + -                  | G-M6       | 22,00     | 350 x 167 x 179            |
| SPG12-75  | 12 V 75 AH   | + -                  | G-M6       | 24,00     | 259 x 168 x 207,5          |
| SPG12-86  | 12 V 86 AH   | + -                  | G-M6       | 24,60     | 350 x 167 x 179            |
| SPG12-90  | 12 V 90 AH   | + -                  | G-M6       | 26,60     | 305 x 168 x 212,5          |
| SPG12-100 | 12V 100 AH   | + -                  | G-M8       | 29,90     | 329 x 172 x 215,5          |
| SPG12-120 | 12 V 120 AH  | + -                  | G-M8       | 37,20     | 407 x 173 x 231            |
| SPG12-135 | 12 V 135 AH  | + -                  | G-M8       | 41,70     | 345 x 172 x 273            |
| SPG12-150 | 12 V 150 AH  | + -                  | G-M8       | 45,70     | 483 x 171 x 218            |
| SPG12-200 | 12 V 200 AH  | + -                  | G-M8       | 62,50     | 522 x 234 x 223            |
| SPG12-250 | 12 V 250 AH  | + -                  | G-M8       | 77,20     | 534 x 271 x 236            |

**Product line:** 12 V AGM batteries  
**Model:** AGM technology, grid plates, sealed, completely maintenance-free  
**Status:** GUG = Filled and charged  
**Quality:** High Performance  
**Storage life:** Up to 12 months

**Type of terminal:** S = plug 6.3 mm  
 G = threaded connection – drilled flat contact  
**Properties:** Extreme high-current capability for short-term discharge  
**Use:** USV + emergency